



TABELLA FLANGE DI ACCOPPIAMENTO ISO 5211

ISO 5211 FLANGES CONNECTION

ISO	NUMERO FORI NUMBER OF HOLES	DIAMETRO FORI Ø DIAMETER OF HOLES	CENTROFORI K PITCH
F.03	4	6	36
F.04	4	6	42
F.05	4	7	50
F.07	4	9	70
F.10	4	11	102
F.12	4	14	125
F.14	4	18	140
F.16	4	22	165
F.25	8	18	254

MOMENTO TORCENTE Nm- Valvole a Farfalla 28W - 28L - 28F

TORQUE VALUES Nm - Butterfly Vaves

NBR / EPDM												
Fluido: H ₂ O Temp.:20°C												
bar	0	6	10	16	20	25	0	6	10	16	20	
DN							DN					
40	12	12	14	15	15	--	300	272	294	362	410	429
50	12	13	14	16	17	20	350	431	557	714	1071	1122
65	12	17	17	19	20	--	400	683	767	893	1470	1540
80	21	32	38	42	44	49	450	1000	1208	1313	1995	2090
100	42	45	47	50	53	65	500	1155	1418	1733	2625	2750
125	50	55	55	74	77	82	600	2300	2800	3700	4800	5280
150	58	63	88	95	99	103	700	3800	5050	5600	6900	7590
200	105	112	189	221	231	320	800	5200	6800	7900	10300	11330
250	175	190	231	336	352	--						